

## Two Door Glass Chiller (Remote)

**Range:** BackBar

**SKOPE ID:** GC402

**Dimensions:** 1585 mm (W) × 590 mm (D) × 870 mm (H)\*

**Capacity:** 290 L

\* Height with legs is adjustable from 855 to 890.

**Project:** \_\_\_\_\_

**Item #:** \_\_\_\_\_



A 2-door under-bar glass chiller designed to keep your bar glasses cool and easily accessible to service staff in busy bars, clubs, and hotels. With a sleek aesthetic, including frameless glass doors, you can create an integrated look for all under-counter glass door bar refrigeration alongside SKOPE's BackBar range. The body is made from powder-coated, galvanised steel with colour options; it can also be upgraded to full stainless steel construction. The cabinet features wire shelving that can accommodate glass racks at either 355 mm × 430 mm, or 430 mm × 430 mm, for keeping your glasses chilled. The glass doors are designed for condensation protection in standard operating environments via the double-glazed, argon-filled, low-e, insulated panels. The glass chiller is a remote version, with self-contained R290 natural refrigerant also available. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty



Natural Refrigerant

© 2023 SKOPE Industries Limited | We reserve the right to alter specifications without notice.


Email: [skope@skope.com](mailto:skope@skope.com)

AUS Freephone: 1800 121 535

NZ Freephone: 0800 947 5673

[skope.com](http://skope.com)





## Cabinet

<b>Type</b>	Glass Chiller		
<b>Finish</b>	Powder-coated galvanised steel or stainless steel		
<b>Insulation (times two)</b>	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)	
<b>Doors</b>	Type	Glass swing door (double-glazed, low-e, argon-filled)	
	Opening Size	Height (mm)	535
Width (mm)		510	
<b>Top Opening (x 2)</b>	Depth (mm)	455	
	Width (mm)	480	
<b>Shelving</b>	Six powder-coated wire shelves		
	1 x fixed bottom shelf (550W x 450D), 1 x fixed bottom shelf (515W x 450D), 2 x adjustable height shelf (550W x 450D), 2 x adjustable height shelf (515W x 450D)		
<b>Lighting</b>	Sign	n.a.	
	Interior	n.a.	
<b>Night Lid</b>	Perspex		

## Dimensions†

	External	Internal	Packed
<b>Width (mm)</b>	1585	1120	TBC
<b>Depth (mm)</b>	590	475	TBC
<b>Height (mm)</b>	855 to 890 (standard legs)		
	725 (plinth)	545	TBC
	820 to 840 (castors)		
<b>Weight (kg)</b>	158	TBC	
<b>Capacity (L)</b>	290		
<b>Footprint (m<sup>2</sup>)</b>	0.94		

## Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet		Multiple cabinets	
			At each joint	At each end wall
Less than 1 metre	±5 mm	±5 mm	+15 mm	
More than 1 metre	-5 mm to +10 mm	-5 mm to +10 mm	+15 mm	

## Performance

<b>Temperature Range (°C)</b>	1 to 4
<b>Maximum Ambient Temperature (°C)</b>	40
<b>Sound Power Level (dB(A))</b>	Standard < 60

## Ventilation

Top	Not required	Sides	Not required	Rear	Not required
-----	--------------	-------	--------------	------	--------------

## Electrical

<b>Supply</b>	220-240 volts a.c., 50 Hz, single phase supply
<b>Cord</b>	1.9 m power cord with 3-pin, 10 amp plug
<b>Current Draw (A)</b>	2.6

## Remote Services

<b>Location</b>	Rear or base
<b>Drain Size</b>	OD 19 mm
<b>Pipe Connection</b>	Liquid line OD 6.35 mm Suction line OD 9.52 mm

## Refrigeration

<b>Controller</b>	SCS Connect
<b>System Type</b>	Remote cartridge
<b>Cartridge Weight (kg)</b>	16
<b>Refrigerant/Charge</b>	Thermostatic expansion valve fitted to suit refrigerant (R134a or R404A standard)/Nitrogen holding charge
<b>Nominal Capacity (W)</b>	n.a.
<b>Heat Rejection (W)</b>	Average n.a. Peak n.a.
<b>Remote Duty (W)</b>	310
<b>Defrost Type</b>	Automatic, off-cycle



GC.2.GSW.r  
on the SKOPE website