



specifications

BB580Xr-3SW

BackBar X Remote Three Door Chiller
Type: RB2413



LED horizontal top light



Side mounted remote refrigeration unit

CABINET DIMENSIONS

	External	Internal
Height:	920mm*	758mm
Width:	1915mm	1580mm
Depth:	590mm	530mm
Floor area:	1.13m ²	

* Height excludes castors, legs and optional worktop.

*Height variation	
Supplied height adjustable castors	1015mm - 1030mm
Supplied height adjustable legs	1050mm - 1080mm
No castors or legs	920mm

Copyright © 2016 SKOPE Industries Limited

CABINET SPECIFICATIONS

Refrigeration system:	Electronically controlled, side mounted, remote refrigeration unit (UE30ABR-100IC), with isolation switch
Electronic controller:	Carel S4 Evo
Refrigerant:	Thermostatic expansion valve fitted as standard to suit R134a or R404A
Remote refrigeration duty:	580 Watts
Cabinet internal volume:	580 litres
Cabinet temperature range:	2°C to 4°C (product mass average)
Climate class:	5
Drainage:	Evaporator drain fitted inside service compartment (requires plumbing)
Electrical:	220-240 Volts a.c. 50 Hz, single phase supply, 0.9 Amps (unit 0.1 Amps)
Internal lighting:	1 x 24W T8 Frosted LED Tube (Ø26 x 1500mm, 5500K) - Switched
Internal door opening size:	3 door openings: 720mm high x 470mm wide
Doors:	3 x self-closing, double glazed, toughened, single Low-E safety glass, frameless look doors. Optional door locks.
Worktop (optional):	Optional 25mm stainless steel worktop
Shelves:	Two adjustable height shelves per door: 495/555mm wide x 440mm deep
Total weight:	160kg

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0442 Rev. 2.1 Feb.2020



SKOPE INDUSTRIES LIMITED



New Zealand Freephone: 0800 947 5673, Fax: (03) 983 3896. Australian Freephone: 1800 121 535, Freefax: 1800 121 533

Email: enquiry@skope.co.nz Website: www.skope.co.nz